

NEW!

LW 400 B MC



The new MC Series from L&W has been created for dive centers, ships, boats and places with limited space. These are suitable for continuous operation and guarantee low maintenance costs due to long service intervals. Comes ready to start. A super lightweight aluminum frame enables mobile applications, combined with very high filling capacity.



Lenhardt & Wagner GmbH

An der Tuchbleiche 39
68623 Hüttenfeld / Germany

Phone: +49 (0)62 56 - 8 58 80 -0

Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com

Internet: www.lw-compressors.com

NEW!

LW 400 B MC



Specifications

- » 4 stroke drive motor
- » Powder coated lightweight aluminium frame in RAL 9006
- » Hour counter
- » Manual condensate drain
- » 2 x Filling hose c/w filling valve
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » Low pressure oil pump
- » Oil filter with bypass
- » Oil- / Water separators after 2nd and 3rd stage
- » Safety valves after each stage
- » 3 x concentric suction/pressure valves
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice
(DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification in accordance to EN 12021
- » 1.7 l filter system (Filter capacity 750 m³ at +20°C)



Rear view

Options

- » Automatic condensate drain incl. collecting tank
- » Automatic stop at final pressure
- » Additional filling hoses c/w filling valves
- » 200 and 300 bar parallel filling pressures
- » Oil- and interstage pressure gauges
- » Oil pressure monitoring c/w auto shut down
- » Additional high pressure outlet
- » Wheel set
- » Air Cooler Connection Kit
- » Switch Over Device 200 / 300bar
- » Puracon filter monitoring

Technical Data

| LW 400 B MC | |
|---|---------------------------------|
| Type: | Air cooled piston compressor |
| Capacity [litre/min] / [Nm ³ /h] / [cfm]: | 400 / 24 / 14 |
| Max. Pressure [bar]: | 350 |
| RPM [1/min]: | 1700 |
| No of cylinders / No of stages: | 3 / 3 |
| Prime mover type: | Vanguard - 4 stroke drive motor |
| Drive power [kW]: | 13.4 |
| Cooling air requirement [m ³ /h]: | 4020 |
| Lubrication type: | Oil pump + Splash oil |
| Oil capacity [litre]: | approx. 1.8 |
| Oil pressure [bar]: | 2.5 (± 0.5) |
| Operating temperature [°C]: | +5°C to +45°C |
| Filter capacity [m ³ at +20°C] ¹⁾ : | 750 (at +20°C) |
| Dimensions W x D x H [mm]: | 1410 x 510 x 826 |
| Weight [kg]: | 171 |
| Noise level (measured at 1 m) [dB(A)]: | 95 |

¹⁾ In accordance with EN 12021

Lenhardt & Wagner GmbH

An der Tuchbleiche 39
68623 Hüttenfeld / Germany

Phone: +49 (0)62 56 - 8 58 80 -0

Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com

Internet: www.lw-compressors.com