



RANGE OVERVIEW

Seaflex Air Lift Bag (ALB) Overview



Air Lift Bags - The Professionals' Choice

Product Details

Versatile

+ Seaflex ALBs are immensely versatile, and ideal for safely supporting and lifting loads at or from any depth. The single point attachment is ideal for lightening underwater static structures such as pipes and templates, or for salvaging vessels from the seabed to the surface. They are robust and highly resistant to damage even in the harshest environments. Our larger ALBs can be surface-towed with their under-slung load at up to 1.5 knots in moderate sea states.

Safe and Efficient

+ Our ALBs have been designed to provide the maximum amount of lift for the least overall height. The design brings with it a wide hem, which aids swifter emptying of the bag on emergency inversion - a notable safety benefit. All our ALBs automatically vent excess air as they ascend dynamically with their load. Their single attachment point helps keep them inherently stable, regardless of load orientation or trim.


Our bags are also more efficiently rigged than others, saving shipping weights without compromising on materials, strength, capability or safety. We understand that time is money, especially during diving operations. Seaflex ALBs address the reality of subsea work: poor visibility, currents and surge, fatigued operators. We understand the challenges of rigging and operating a lift bag in less than ideal conditions underwater. Our ALB range has been developed not as a theoretical exercise by a desk jockey, but in conjunction with actual living, breathing users to make it as diver-friendly as anything in its class.

Tested and Proven

+ The ALB range is, like every Seaflex product, carefully designed, constructed and tested to meet and exceed demanding international standards. As you would expect, Seaflex ALBs fully comply with IMCA D-016 guidelines. But, uniquely within our market, we have drop-tested our ALBs to prove their safety factors and we have tested and demonstrated the performance of our inverter lines. The result? You can rely on Seaflex ALBs to perform safely, effectively and predictably, time after time and year after year. All our ALBs are delivered ready for immediate use with a universally compliant documentation: a unit-specific log book containing certification, service records and operating manual. Another benefit: our ALBs require remarkably little storage space relative to their lift capacity; ALBs capable of 350 tonnes of lift can be stored on a 6 x 6 metre footprint and weigh less than 3.5 tonnes.

Off the Shelf or Made to Measure

+ There is most probably an existing Seaflex ALB, or ALB combination, suitable for your exact subsea lifting task. But if there isn't, then our team will draw upon their long experience in this field to design and manufacture a bag to suit your exact requirements.



E. buoyancyballast@uniquegroup.com
W. www.uniquegroup.com

Air Lift Bags - The Professionals' Choice


Key Features and Benefits at a Glance

For Your Peace of Mind

- + Fully compliant with IMCA D-016, and with ABS PDA.
- + 7:1 design WLL factor on the strops.
- + Overall assembly tested and proven to a 5:1 minimum WLL safety factor. Independent Type Test Certificates are available.
- + Tested and proven inverter line attachment point.
- + High performance structural fabric canopy.
- + RF welded seams.
- + Rental units inspected and tested between every single job.

For Your Ease of Operation

- + Seaflex DeeTangler™ to enable simple "sort and check" of the strops subsea to avoid twisting and overloading.
- + Unique strop i/d system terminating in a closed ring: no risk of incorrect connection leading to in-service failure.
- + Integral handling ladders on units over 1 ton.
- + 3/4 inch BSP standard inflation valve with 316 stainless steel Camlock end fitting standard on ALBs of 2 tons and above.
- + Base-operated high flow dump valve.
- + Industry-leading height to weight ratio: maximising load freeboard where required.
- + Design service available, to provide optimised solutions for specific tasks.
- + Delivered in an enclosed crate and ready for immediate use with universally compliant documentation: ALB specific log book containing certification, service records and operating manual.



Model No	Inflated			Weight		Packed		
	Lift (Kg)	H x Ø (Mtr)	H x Ø (Ft)	Kg	Lbs	L x W x D (Mtr)	L x W x D (Ft)	No/pallet
250 ALB	250	1.3 x 0.9	4.27 x 2.95	3	6.61	0.4 x 0.2 x 0.4	1.3 x 1.3 x 1.1	40
500 ALB	500	1.7 x 1.2	5.58 x 3.94	5	11	0.5 x 0.3 x 0.5	1.6 x 1.0 x 1.6	30
1t ALB	1,000	1.9 x 1.6	6.23 x 5.25	11	23	0.6 x 0.4 x 0.6	2.0 x 1.3 x 2.0	20
2t ALB	2,000	2.5 x 1.8	8.20 x 5.91	23	51	0.8 x 0.4 x 0.8	2.6 x 1.3 x 2.6	10
3t ALB	3,000	3.2 x 2.0	10.50 x 6.56	32	71	0.8 x 0.4 x 0.8	2.6 x 1.3 x 2.6	6
5t ALB	5,000	3.7 x 2.0	12.14 x 6.56	38	84	0.9 x 0.5 x 0.9	3.0 x 1.6 x 3.0	5
10t ALB	10,000	4.5 x 2.4	14.76 x 7.87	75	165	1.2 x 0.5 x 1.2	3.9 x 1.6 x 3.9	3
15t ALB	15,000	5.4 x 2.7	17.72 x 8.86	110	243	1.2 x 0.6 x 1.2	3.9 x 2.0 x 3.9	2
20t ALB	20,000	5.5 x 3.2	18.04 x 10.50	120	265	1.2 x 0.7 x 1.2	3.9 x 3.0 x 3.9	2
25t ALB	25,000	5.9 x 3.8	19.36 x 12.47	175	386	1.2 x 0.9 x 1.2	3.9 x 3.0 x 3.9	1
35t ALB	35,000	6.5 x 4.0	21.33 x 13.12	230	507	1.4 x 1.2 x 1.4	4.6 x 3.9 x 4.6	1
50t ALB	50,000	8.2 x 4.5	26.90 x 14.76	416	917	2.6 x 1.22 x 0.96	8.5 x 4.0 x 3.1	1



Unique Group

E. buoyancyballast@uniquegroup.com
 W. www.uniquegroup.com

Providing and Proving Seaflex ALB Testing

Whereas other companies simply look to sell their versions of our ALBs, Seaflex has gone further than anyone in the market in proving our designs and our products via rigorous and documented testing of both their structural integrity and their ability to invert during operation. Why? To give our customers complete peace of mind, given that the safety of their personnel is at stake.

Independently Overload-Tested

+ Seaflex engineers every ALB from 25 kg to 50,000 kg to a 7:1 WLL ratio, well exceeding the IMCA D-016 design requirement of 5:1. And then we go another step further than even IMCA stipulates: we have chosen to Type Test every model of ALB from 25 kg to 35,000 kg to a minimum of the IMCA figure of 5:1. Seaflex conducts these Type Tests at the TÜV National Engineering Laboratory in Glasgow. The Type Tests are performed by dropping and then catching the water-filled ALB to produce a shock overload, testing the fabric integrity, strapping arrangement and hardware of each type of ALB. A Certificate of Conformity to the Type Test is then supplied as part of the documentation pack for with each and every Seaflex ALB.

Inversion Strongpoints Tested and Proven Subsea

+ IMCA D-016 stipulates that a clearly designed strong point is built into all parachute-type bags for attachment of a suitable inverter line. However, there is no IMCA requirement to test if this will work in a scenario where a bag is suddenly released as a result of attachment failure, rapidly accelerating to produce a shock load on the previously slack inverter line and its attachment point. So in this further respect, Seaflex have again gone over and above the minimum industry requirements to demonstrate that our ALBs will perform exactly as they need to: we conducted full-scale subsea testing, suddenly releasing fully filled ALBs against their inverter lines. And as you would expect, our ALBs came through these tests with flying colours, and with measured overload strength to spare. So our clients can be completely assured that Seaflex ALBs will invert to design, rather than surfacing at high speed and getting caught up in the thrusters of their support vessel.



Unique Group

E. buoyancyballast@uniquegroup.com
W. www.uniquegroup.com



Technology, Service and Support

Manufacturing Technology

+ All Seaflex products are designed and manufactured in the UK. Our bag canopies are constructed from High Tensile Trevira® Polyester base cloth (either 2 /2 or 3 /3 fibre panama pattern weave) coated with heavy duty UV stabilised PVC coating or, for special applications, polyurethane. Trevira is incredibly strong; a 50 mm wide 3/3 strip has a break load of approximately 1 tonne. The panels for our bags are precision cut on our 15 metre long, 3 metre wide advanced automated table for perfect repeatability. Once inspected and approved panels are assembled by skilled personnel to using Radio Frequency welding to strict quality control standards.

Certification

+ All our work is carried out within a system which complies with the ISO 9001-2009 Quality Management Standard as audited by Lloyds Register Quality Assurance for full traceability – and we have now gained ISO 14001 and ISO 18001 accreditation.



Service

+ Whether for hire or sale, all Seaflex products are sent out fully tested and inspected against their build criteria. And we do also offer on-site support to our clients in the use of our products – this most often happens within the more complex buoyancy applications for our products.

In the event that your Seaflex product should suffer minor damage in service, we can supply an approved, boxed field service kit comprising of patches, a professional quality heat gun and instruction manual to make good minor leaks prior to product refurbishment.

We can also advise on the viability of carrying out more extensive repairs, which would typically be undertaken either at our factory or at one of our approved service centres.

Support

+ Our support philosophy is "Wherever, Whenever". This underlines the Seaflex commitment to not just sending out tested, proven products in proper shipping crates and with the most comprehensive documentation package in the business – but to assisting our customers in every way possible throughout their time using our products, whether the job is a hire project or an equipment sale.

We offer worldwide support to our customers via either email or phone from head office in the UK and via our ever-growing network of offices and partners around the world.

You can put your trust in Seaflex – we won't let you down.





Local presence
worldwide

UNIQUE GROUP OFFICES

MIDDLE EAST

UAE

Unique Group FZC
Sharjah
T. +971 6 5130333
E. uaesales@uniquegroup.com

QATAR

Unique System Tr & Eng WLL
Doha
T. +974 44147079
E. qatarsales@uniquegroup.com

SAUDI ARABIA

Muraba Alsahra Trading LLC
Riyadh and Al Khobar
T. +966 13 802 0614
E. ksasales@uniquegroup.com

ASIA PACIFIC

SINGAPORE

Unique System (SEA) Pte Ltd
Singapore
T. +65 6542 1800
E. fareastsales@uniquegroup.com

INDIA

Unique Hydrographic Systems Pvt Ltd
Navi Mumbai and Vadodara
T. +91 22 27619939/40/41/75
E. indiasales@uniquegroup.com

AUSTRALIA

PERTH

Unique Subsea Australia Pty Ltd
Perth Airport Park
T. +61 418 205 212
E. aussales@uniquegroup.com

QUEENSLAND

Unique Subsea Australia Pty Ltd
Pinkenba, Queensland
T. +61 418 205 212
E. aussales@uniquegroup.com

USA

CENTRAL

Unique System Inc
Houston, Texas
T. +1 713 937 6193
E. usasales@uniquegroup.com

EAST COAST

Water Weights Inc
Suwanee, Georgia
T. +1 678 730 4180
E. buoyancyballast@uniquegroup.com

WEST COAST

Water Weights Inc
Montclair, California
T. +1 909 626 8316
E. buoyancyballast@uniquegroup.com

AFRICA

SOUTH AFRICA

Unique Hydra (Pty) Ltd
Cape Town
T. +27 21 835 7900
E. sasales@uniquegroup.com

NIGERIA

Unique Charkin System Ltd
Port Harcourt
T. +234 908 5659444
E. nigeriasales@uniquegroup.com

EUROPE

UK

Unique Seaflex Ltd
Cowes, Isle of Wight
T. +44 1983 290 525
E. buoyancyballast@uniquegroup.com

Unique System (UK) Ltd

Water Weights Ltd
Aberdeen, Scotland
T. +44 1224 723 742
E. uksales@uniquegroup.com

NETHERLANDS

Unique System BV
T. +31 850 513 700
Water Weights BV
T. +31 850 513 750
Werkendam
E. info.wwnl@uniquegroup.com

Unique Group's Buoyancy & Ballast products are available for hire or purchase from more than 20 other worldwide locations via our network of independent partners. Please contact us for more details.