

### Chamber Communicator Single-Lock

**Description:**

This Single Lock Chamber Communicator features a 110/220VAC with internal 12VDC Battery Back-Up and a Battery Condition Indicator.

**Specifications:**

Length: 273mm  
 Width: 172mm  
 Height: 177mm  
 Weight: 5.1kg  
 (without batteries)



**Order Detail:**

Single Lock - Chamber Communicator With Microphone , 12VDC External Supply Only	D-C-489
---	---------

### Chamber Communicator Twin-Lock

**Description:**

The most unique feature of these versatile and powerful Rack Mount Communicators, is the design of separate channels and volume controls for each diver and tender, both for the up-link and the down-link paths. These communicators come standard with rear mounted MS connector, providing connections to diver and tender inputs and outputs. All rack mount radios include a Hand-Held Push-To-Talk Microphone. You can set the volume for each diver and tender to their individual comfort level. Both divers can be set up on Simulcom or Push-To-Talk, or one diver on Simulcom and the other diver on Push-To-Talk mode, or any combination of the two modes. The rechargeable Gel-cell type battery automatically recharges while operating the unit. The voltage is automatically selected for 110/220VAC, 50/60Hz, with built in isolation transformer. The unit features a Battery Condition Indicator.

**Specifications:**

Length: 257mm  
 Width: 203mm  
 Height: 191mm  
 Weight: 6.8kg  
 (without batteries)  
 Battery Back-Up:  
 110/220VAC, Internal 12VDC  
 Power: 115/230VAC, 50/60Hz  
 Rear connector input / output:  
 MS 14 pin, Male & Mating  
 Connector  
 Enclosure:  
 19" black anodised aluminum  
 rack  
 Back-up Battery:  
 12VDC rechargeable Slide  
 Terminal Gel-cell batteries  
 Battery Life: 15 hours (approx.)



**Order Detail:**

Twin Lock - Chamber Communicator, AC Powered With Battery Back Up And Microphone	D-C-490
--	---------

