

4-Deck Camera Control Rack

Description:

The 4-Deck Camera Control Rack is designed to power 4 x 12Vdc CCTV cameras. The Camera Control Rack has a 2U, 19inch rack form factor. This Rack complies with the requirements set out in IMCA, ABS and DNV.

Features:

- Each output is powered by a dedicated medical grade switch mode power supply providing galvanic isolation (no direct conduction path) between the supply and output to each individual camera.
- The cameras are individually controlled via the control switches located on the front of the rack.

Specifications:

Power Source:
115 – 230Vac 50/60Hz
Power Consumption:
1.2A/115Vac 0.7/230Vac
Power Output:
12Vdc 3.7A Max per Camera
Width: 483mm
Height: 88mm
Depth: 335mm
Weight: +-5kg



Order Detail:

| | |
|----------------------------|-------------|
| 4-Deck Camera Control Rack | D-EE-197 |
| Deck Camera and 20m Cable | D-EE-197-01 |

4-Zone Fire Alarm Rack

Description:

The 4-Zone Fire Alarm rack can monitor four individual zones or locations. In the event of an alarm condition an audible and visual alarm is triggered at the Fire Alarm rack indicating the location of the fire. This Rack complies with the requirements set out in IMCA, ABS and DNV.

Features:

- The Fire Alarm Rack has a 2U, 19inch rack form factor
- A flashing sounder indicator is provided that can be placed at the operators discretion
- The Fire Alarm makes use of Apollo Fire's ORBIS Marine Optical Smoke Detectors
- Four monitored inputs
- Sensor series connection

Specification:

Power Source:
115 – 230Vac 50/60Hz
Power Consumption:
1.2A/115Vac 0.7/230Vac
Voltage to Sensor: 24Vdc
Width: 483mm
Height: 88mm
Depth: 335mm
Weight: +-5kg



Order Detail:

| | |
|------------------------|----------|
| 4-Zone Fire Alarm Rack | D-EE-198 |
|------------------------|----------|