



**Specification:**

Model:	GB 24 - 24 Cylinders	GB 64 - 64 Cylinders
		
Cylinders	24	64
Length x Width x Height	± 1450 x 1030 x 2015mm ± 57.09" x 40.55" x 79.33"	± 1800 x 2100 x 2300mm ± 70.87" x 47.24" x 90.55"
Weight	± 2600kg	± 6400kg

**Order Detail:**

24 x 50 litre Cylinder Heliox Bank (200 bar) – Heliox	D-GB-433
64 x 50 litre Cylinder Heliox Bank (200 bar) – Heliox	D-GB-435

**DNV Gas Banks**

**Description:**


These 200 bar Seamless cylinder gas banks are supplied in a DNV 2.7-1-OFFSHORE 12/16-cylinder quad Mild Steel frame with pad eyes for lifting, a DNV certified lifting sling is included. These 50 litre cylinders can be supplied with one or two inlet and one or two outlet

configurations (with gauges) and are painted as per IMCA for use with air, oxygen or heliox requirement.

**Features:**

- For air quads: stainless steel pipes and tubing
- For Oxygen/Heliox quads: Tungum tubing & Victor or Tescom Regulators
- DNV 2.7-1 Certification pack for lifting frame and slings
- IMCA D018 - Certification for the Cylinder Assembly

**Specification:**

Model:	GB 16 - DNV
	
Cylinders	16
Length x Width x Height	1100mm x 1100mm x 2220mm
Tare Mass	500 kg
Pay Load	1600kg
Gross Mass	2100 kg

**Order Detail:**

16 x 50L, 200bar Nitrox Cylinder Gas Bank- DNV Quad Frame and Sling	D-GB-437
16 x 50L, 200 bar, Heliox Cylinder Gas Bankk- DNV Quad Frame and Sling	D-GB-438
16 x 50L, 200 bar, Oxygen Cylinder Gas Bankk- DNV Quad Frame and Sling	D-GB-439