

HD 45, Hammer Drill**Description:**

The Stanley Hydraulic HD45 Hammer Drill is a heavy duty underwater drill designed for drilling in concrete, rock and masonry. The feathering on/off valve and adjustable rotation speed allows easy drill bit start-up and precise control. The high torque rotation motor drives standard 736 Skil hex carbide tipped drill bits and is capable of drilling a 2 inch diameter hole up to 29 inch deep. Fluted drill bits require no water or air to clear holes. Ideal for drilling holes for setting anchor bolts.

Features:

- T-Handle with large on/off trigger for precise control
- Stainless Steel spools and fasteners
- Forward-Reverse with adjustable bit rotation speed
- Feathering on/off valve allows easy start and control
- Uses 736 Skil fluted carbide tipped drill bits - requires no

water/air to clear holes

- Drills ¾" to 2" diameter holes, up to 29" deep and core drills up to 4" in diameter
- Operates in any position
- Painted hi-visibility yellow
- Trouble free drill steel latch retainer

Specifications:

Chuck Capacity: Up to 2" dia. or 4" core bit
 Steel Capacity: 736 Skil hex
 Circuit Type: Open Center
 Flow Range: 7-9gpm / 26-34lpm
 Optimum Flow: 8gpm / 30lpm
 Working Pressure: 1500 - 2000psi / 105 - 140bar
 Full Relief Setting: 2250psi / 155bar
 Rotation Speed: 0 - 300RPM
 Weight (less tool bit): 49lbs / 22.2kg
 Length: 24½" / 62.2cm
 Width (at handles): 14" / 35cm
 Hydraulic Ports: -8 SAE O-ring
 Hose Whips: Yes (3/8" NPT Male thread)

**Order Detail:**

HD45-Stanley Hammer Drill OC, NO. 736 Skil Hex,	D-ST-153
---	----------