

Aquadopp 6000 m



High-performance full ocean depth, single-point current meter with titanium housing

With all the features and capabilities of the standard Aquadopp, the deepwater Aquadopp 6000 m current meter has been used and proven by oceanographers around the world for almost 20 years. Thanks to innovative data diagnostic features for challenging environments, it provides exceptionally high-quality 3D currents in a form factor that is easy to install in any type of mooring line configuration, or simply attached to a bottom or surface platform.

Raw magnetometer data can be stored for post calibration of compass when used without the inductive modem option.



Aquadopp 6000 m

Highlights

- ✓ Full ocean-depth single-point current meter
- ✓ Titanium housing
- ✓ Diagnostics mode for mooring performance evaluation

Applications

- ✓ Studies of deep-water currents
- ✓ Studies of tidal currents
- ✓ Attached to mooring lines
- ✓ Measurements of unaffected currents from physical structures
- ✓ In conjunction with riser monitoring systems
- ✓ Alternative to conventional current meters with errors due to fouling
- ✓ Combination of currents and high-accuracy CTD data
- ✓ Near-bed current measurements from landers
- ✓ Deep ocean mining support

Aquadopp 6000 m

Technical specifications

→ Water velocity measurements

Maximum profiling range	N/A
Cell size	0.75 m
Minimum blanking	0.50 m
Maximum number of cells	1
Measurement cell position	0.5-5.0 m (user-selectable)
Default position (along beam)	0.50-2.0 m
Velocity range	±5 m/s
Accuracy	±1% of measured value ±0.5 cm/s
Velocity precision	Consult instrument software
Maximum sampling rate(output)	1 Hz
Internal sampling rate	23 Hz

→ Echo intensity

Sampling	Same as velocity
Resolution	0.45 dB
Dynamic range	90 dB
Transducer acoustic frequency	2 MHz
Number of beams	3
Beam width	3.4°

→ HR option

Maximum profiling range	N/A
Cell size	N/A
Minimum blanking	N/A
Maximum number of cells	N/A
Range/Velocity limitations	N/A
Accuracy	N/A
Max. sampling rate	N/A

→ Z-Cell option

Aquadopp 6000 m

Cell zero acoustic frequency	N/A
------------------------------	-----

Maximum profiling range	N/A
-------------------------	-----

Number of beams	N/A
-----------------	-----

→ Sensors

Temperature:	Thermistor embedded in head
--------------	-----------------------------

Temp. range	-4 to +40 °C
-------------	--------------

Temp. accuracy/resolution	0.1 °C/0.01 °C
---------------------------	----------------

Temp. time response	10 min
---------------------	--------

Compass:	Magnetometer
----------	--------------

Accuracy/resolution	2°/0.1° for tilt < 20°
---------------------	------------------------

Tilt:	Liquid level
-------	--------------

Accuracy/resolution	0.2°/0.1°
---------------------	-----------

Maximum tilt	30°
--------------	-----

Up or Down	Automatic detect
------------	------------------

Pressure:	Piezoresistive
-----------	----------------

Range	6000 m
-------	--------

Accuracy/precision	0.5% FS / 0.005% of full scale
--------------------	--------------------------------

→ Analog inputs

No. of channels	2
-----------------	---

Supply voltage to analog output devices	Three options selectable through firmware commands: 1) Battery voltage/500 mA, 2) +5 V/250 mA, 3) +12 V/100 mA
---	--

Voltage input	0-5 V
---------------	-------

Resolution	16 bit A/D
------------	------------

→ Data recording

Capacity	9 MB, can add 4/16 GB
----------	-----------------------

Data record	40 bytes
-------------	----------

Diagnostics record	40 bytes
--------------------	----------

Wave record	N/A
-------------	-----

Mode	Stop when full (default) or wrap mode
------	---------------------------------------

→ Real-time clock

Accuracy	±1 min/year
----------	-------------

Aquadopp 6000 m

→ Real-time clock

Backup in absence of power 4 weeks

→ Data communications

I/O RS-232 or RS-422

Communication baud rate 300-115200 Bd

Recorder download baud rate 600/1200 kBd for both RS-232 and RS-422

User control Handled via "Aquadopp" software, ActiveX® function calls, or direct commands with binary or ASCII data output

→ Connectors

Bulkhead MCBH-8-FS titanium

Cable PMCIL-8-MP on 10 m polyurethane cable

→ Software

Functions Deployment planning, instrument configuration, data retrieval and conversion (for Windows®)

→ Power

DC input 9-15 V DC

Maximum peak current 3 A

Avg. power consumption 0.015 W

Sleep current < 100 µA

Transmit power 20 W

→ Batteries

Battery capacity 50 Wh (alkaline or Li-ion), 165 Wh (lithium), Single or dual

New battery voltage 13.5 V DC (alkaline)

→ Environmental

Operating temperature -5 to +40 °C

Storage temperature -20 to +60 °C

Shock and vibration IEC 721-3-4

EMC approval IEC 61000

Depth rating 6000 m

→ Materials

Standard model Titanium and POM



Aquadopp 6000 m

→ Dimensions

Maximum diameter	84 mm
Maximum length	~500 mm (single battery), +110 mm (double battery) depending on head configuration

→ Weight

Weight in air	7.6 kg
Weight in water	4.8 kg

→ Options

1) Alkaline, lithium or Li-ion external batteries, 2) Inquire for different head configurations, 3) Inductive modem